

HC-PTW




- Rated current50A~300A
- Two circuits can be measured at the same time
- Ferrite core specification also available (Rated current...50A~100A)

Applications

Inverters, power supply equipment, NC machine tools

Dimensions

(mm)



Specification

Ta=25°C

Type	HC-PTW050V4B15	HC-PTW100V4B15	HC-PTW150V4B15	HC-PTW200V4B15	HC-PTW300V4B15
Rated current [If]	±50A	±100A	±150A	±200A	±300A
Saturation current [Is]	±150A	±300A	±450A	±600A	±600A
Linearity limits	0~±150A	0~±300A	0~±400A	0~±400A	0~±400A
Rated output [Vh]	±4V±1%				
Residual output [Vo]	Within ±50mV				
Output linearity	Within ±1%				
Response time	Within 10μs (at di/dt=100A/μs)				
Output Temp. Coef.	Within ±0.1%/°C				
Residual output Temp. Coef.	Within ±4mV/°C	Within ±3mV/°C		Within ±2mV/°C	
Control power supply	±15V±5%				
Operating Temp.	-10°C~+75°C				
Storage Temp.	-15°C~+85°C				
Dielectric withstand voltage	2500V AC 50/60Hz 1minute				
Insulation resistance	Not less than 500MΩ 500V DC				

Note1) The indicated rated output is the one when no load is applied.


Note2) The indicated residual voltage is the one after the core hysteresis is removed.

Characteristics chart


HC-PTW100V4B15

Time base : 5μs/div.


Pulse current response characteristic




Noise characteristics (Effects of dv/dt)



Noise characteristics (Effects of impulse noise)



Input/output characteristics



Note : The mark "◁" means 0V or 0A.